



Spherical joints.

Inch range, acc. to DIN 12264/12244. PRECISO.

S	O. D. mm	Length mm	Wall thick. mm	Balls form B (D)	Sockets form A (C)
13/2	8	100	2.7	0.125.002	0.126.002
13/5	8	100	1.5	0.125.005	0.126.005
19/9	13	100	1.5	0.125.009	0.126.009
29/15	19	120	1.8	0.125.015	0.126.015
35/20	24	120	1.8	0.125.020	0.126.020
40/25	30	150	2.0	0.125.025	0.126.025
41/25	32	150	2.0	0.125.026	0.126.026
51/30	36	150	2.8	0.125.030	0.126.030
64/40	48	150	3.2	0.125.040	0.126.040




*mm range on request


Flasks, round bottom, center neck.
 With spherical joint.

Capacity ml	S	Flasks O. D. mm	Height mm	Plastic- coated
100	35/20	64	110	0.644.100 0.645.100
250	35/20	81	140	0.644.250 0.645.250
500	35/20	105	170	0.644.500 0.645.500
1000	35/20	126	210	0.644.001 0.645.001
2000	35/20	166	260	0.644.002 0.645.002
4000	35/20	207	310	0.644.004 0.645.004

Clips for spherical joints,
 with screw.

S	
13/2-13/5	0.133.013
19/9	0.133.019
29/15	0.133.029
35/20	0.133.035
40/25-41/25	0.133.040
51/30	0.133.051
64/40	0.133.064


Adapters with standard/spherical joints. PRECISO.

ST	S	
NSH 19/32	KSK 35/20	0.530.035
NSK 29/32	KSP 35/20	0.520.029