




**Timer, with bell 0-60 min., plastic housing.**

Type	
Standing	8.480.112



**Stopwatches, Trackstar, dia. 53.5 mm. Pinlever movement, 7 jewels, shock protected, chromed metal case.**

Type	
Crown stopper 1/5 s, 0-30 min	8.482.100
Addition stopper 1/10 s, 0-15 min	8.482.200
Crown stopper 1/5 s, 0-60 min	8.482.300



**Mechanical table stopwatch, with minutes and seconds-scale, scale dia. 95 mm, height approx. 130 mm, for recording periods from 1 second to 60 minutes, running time about 20 hours, housing made of plastic, black, movement is wound with key on the back, with start/stop and zero-fly-back-levers.**

Type	
	8.481.250

**Multi-function-quartz-stopwatch, recording period 50 minutes, 59 seconds and 99/100 seconds, 6 digit LCD-display. Functions: start/stop, addition, split, reset, battery operated (1.5 V - life time about 2 years), ABS-housing.**

Type	
	8.484.150





**Quartz LCD-counter** with alarm, precise second setting up to 99 minutes, alarm up to 60 seconds, complete with clip, stand and magnet, battery operated (1.5 Volt button cell), Size: 63x58x12 mm, Weight: 40 gramms.

Type	8.484.160
------	-----------



**Multi-timer**, can be used as stopwatch, programmable timer, etc., with signal, the perfect multi-timer for all control applications in laboratories, industries etc., as timer programmable up to 99 minutes, 59 seconds, as stopwatch applicable 59 minutes, 59 seconds, even as addition stop-watch applicable (start/stop/start...reset), accuracy  $\pm 0.5$  sec./day, battery operated (1.5 V), can be used as table timer, or as wall timer (with magnet or clip), or as stick-on unit (with clip), dimensions 70x70 mm.

Type	8.484.200
------	-----------

**WITEG-digital-tally counter**, 4 figure hand-operated reset counter, with handy thumb ring for easy operation, chromeplated steel housing, counting range 0-9999.

Type	8.481.050
------	-----------

